



Manila

camira

Photographic fabric scans are not color accurate. Always request actual fabric samples before ordering.



Cambric
MNL01



Mist
MNL05




Ore
MNL04



Semolina
MNL02




Bran
MNL03



Heavens
MNL06



Bask
MNL07



Satsuma
MNL15




Stalk
MNL08



Foil
MNL20



Grapefruit
MNL17



Leafy
MNL12



Fuel
MNL21



Rosette
MNL11



Cerulean
MNL09



Char
MNL16



Mulled
MNL14



Seaway
MNL13



Liquorice
MNL19



Tamarind
MNL10



Transport seating



Anti-microbial



Phthalate free



Year guarantee

Manila combines the high performance of vinyl with the soft appearance of textile. It's an environmentally preferable phthalate free vinyl, with a knitted cotton backing and an attractive printed design. It features a lightly textured surface effect which works naturally alongside other transport fabrics or as a standalone seating option.

Technical information

EN

Composition

Surface: 100% PVC
Substrate: 100% Cotton

Width

54 inches minimum

Weight

23^{1/2} oz/sq yd ±5% (35^{1/2} oz/running yd ±5%)

Flexes

ISO 7854 Method B 400,000 Flexing cycles

Abrasion Resistance

Heavy duty / 5 year guarantee (full details available)
ISO 5470-2 100,000 rubs
(Grade 2 minimum)

Flammability

FMVSS 302
FAR/JAR 25.853
Note: Flammability performance is dependent on components used. Our certificates show what substrates have been used in our tests. For composite tests customers must ensure their complete furniture meets the necessary standards.

Light Fastness

6 (EN ISO 105 B02)

Hot Light Fastness

>6 (ISO 105 - B06)

Fastness to Rubbing

Wet: 4 Dry: 4 (EN ISO 105 X12)

Phthalate free

EN ISO 15777

Anti-microbial / Anti-fungal

AATCC 147

Maintenance

Vacuum regularly. Wipe with a damp cloth using soap and water or use proprietary upholstery shampoo. For deeper cleaning use bleach or alcohol. For full details, see vinyl technical guide.

Color Matching

Batch to batch variations in shade may occur within commercial tolerances.

The Unregistered Design Rights and the Copyright in all designs are the exclusive property of Camira Fabrics Limited.

F

Composition

Surface: 100% PVC
Inférieure: 100% Coton

Largeur

54 pouces minimum

Poids

23^{1/2} oz/sq yd ±5% (35^{1/2} oz/yd.lin ±5%)

Flexes

ISO 7854 Method B 400,000 Flexing cycles

Résistance à l'abrasion

Usage intense / garantie 5 ans (renseignements complémentaires disponibles)
ISO 5470-2 100,000 frottements
(Grade 2 minimum)

Flammabilité

FMVSS 302
FAR/JAR 25.853
Note: La performance de flammabilité dépend des composantes utilisées. Nos certificats indiquent les substrats utilisés dans nos tests. Pour les tests composites, les clients doivent s'assurer que leurs meubles complets satisfont aux normes nécessaires.

Solidité à la lumière

6 (EN ISO 105 B02)

Solidité à la lumière chaude

>6 (ISO 105 - B06)

Solidité au frottement

Mouillé: 4 Sec: 4 (EN ISO 105 X12)

Sans phthalate

EN ISO 15777

Anti-microbial / Anti-fungal

AATCC 147

Nettoyage

Passez l'aspirateur régulièrement. Essuyez avec un chiffon humide avec de l'eau et du savon ou utilisez un shampooing pour tissus d'ameublement exclusif. Pour un nettoyage en profondeur, utilisez la javel ou alcool. Pour des détails complets, veuillez consulter notre manuel technique pour nos gammes vinyles.

Standardisation des coloris

Variations de coloris d'un bain à un autre peuvent se manifester.

The Unregistered Design Rights and the Copyright in all designs are the exclusive property of Camira Fabrics Limited.

ES

Composición

Superficie: 100% PVC
Sustrato: 100% Algodón

Ancho

54 pulgadas mínimo

Peso

23^{1/2} oz/sq yd ±5% (35^{1/2} oz/lin.y ±5%)

Flexes

ISO 7854 Method B 400,000 Flexing cycles

Resistencia a la abrasión

Garantía de 5 años con uso intenso (más información disponible bajo consulta)
ISO 5470-2 100,000 rubs
(Grade 2 minimum)

Inflamabilidad

FMVSS 302
FAR/JAR 25.853
Note: El rendimiento de la inflamabilidad depende de los componentes usados. Nuestros certificados muestran qué substratos se han usado en nuestros tests. Para tests compuestos nuestros clientes deben asegurar si sus muebles cumplen la normativa al uso.

Solidez a la luz

6 (EN ISO 105 B02)

Solidez a la luz caliente

>6 (ISO 105 - B06)

Solidez al rozamiento

Húmedo: 4 Seco: 4 (EN ISO 105 X12)

Sin ftalatos

EN ISO 15777

Anti-microbial / Anti-fungal

AATCC 147

Limpieza

Uso aspirador regularmente. Limpiar con un trapo usando jabón y agua o producto limpieza para tapicerías. Para una limpieza más profunda use lejía o alcohol. Para más detalles, ver guía completa de limpieza vinilo.

Continuidad de colores

Cada tintada puede tener pequeñas variaciones en el tono dentro de las tolerancias comerciales aceptadas.

The Unregistered Design Rights and the Copyright in all designs are the exclusive property of Camira Fabrics Limited.